# **Model 226T**

**Kingston Vertical Check Valve** 




### **Features**

- Designed for Lubricated or Non-Lubricated Air Compressors
- Stainless Steel Spring
- Maximum Temperature is 350°F
- Available Sizes: 1/4" NPT & 3/8" NPT

Model	Inlet Size	Outlet Size	Cracking Pressure (PSI)	Dimensio Height (A)	ons (inches) Hex (B)	Max. Temp (°F)	Figure/Part No.
226T	1/4" NPT	1/4" NPT	1.5	2-1/32"	7/8"	350°F	226T-2-2
	3/8" NPT	3/8" NPT	1.5	2-5/32"	7/8"		226T-3-3

### **Materials**

No.	Part Name	Materials
1	Body	Brass
2	Brushing	Brass
3	Spring Seat	Brass
4	Retaining Ring	Beryllium Cooper
5	Disc	Teflon
6	Spring Seat	Stainless Steel




## Kingston Model 226T Vertical Check Valve

### **Flow Capacity Information**

Fig. 226T - 1/4" x 1/4"


Fig. 226T - 1/4" x 1/4"

600
550
500
450
450
200
150
200
150
200
150
PRESSURE, PSIG



### **Ordering Information**

Kingston Vertical Check Valves
Part Number Codes



### **Product Notes**

All Kingston Check Valves are manufactured under a quality control system approved by the National Board of Boiler and Pressure Vessel inspectors.

Storm Manufacturing Group, Inc. reserves all rights. Product specifications and designs are subject to change without notice.

The information contained herein by Storm Manufacturing Group (SMG) is provided in good faith and as a product guide only. Further, SMG makes no representation as to the completeness or accuracy of the information contained herein. Any person or persons using the information contained herein must exercise their own judgement and consider all local, regional, national and global safety standards in evaluating valve selection options. Final application design and integration of Kingston Products are the sole responsibility of the end user.

