

Model 259

Quick Opening Industrial Flow Control Valve




Features

- Durable, Light-Weight, High Performance Flow Control
- Designed for Liquid, Compressed Air or Gas Applications
- Developed For Use in Car Wash, Carpet Cleaning and Other Systems that Require Durable Control Valve Using Mechanical Contact to Operate the Valve
- Maximum Operating Pressure is 150 PSI
- Treaded Stem Provide Alternative Mounting Option
- Alternative Seals Available
- Alternative Disc, Lever and Cap Options May Be Available. Please Call for Details.

| Model | Inlet Size | Outlet Size | Dimensions | | | Approx. Shipping Wt. | Min. Temp | Min. Temp |
|-------|------------|-------------|------------|---------------|-----------|----------------------|-----------|-----------|
| Model | | | Height (A) | Thickness (B) | Width (C) | Approx. Shipping Wt. | (°F) | (°F) |
| 259 | 1/4" NPT | 1/4" NPT | 2" | 13/16" | 2-13/64" | 5 oz. | -40°F | 225°F |


Materials


| No. | Part Name | Materials |
|-----|--------------|-----------------|
| 1 | Body | Brass |
| 2 | Сар | Brass |
| 3 | Stem | Brass |
| 4 | "O" Ring | EPM |
| 5 | Disc | EPM |
| 6 | Disc Cage | Brass |
| 7 | #6 Screw | Stainless Steel |
| 8 | Spring | Stainless Steel |
| 9 | Lock Washer | Bronze |
| 10 | Hex Lock Nut | Brass |
| 11 | Loctite | Loctite |



Kingston Model 259 Quick Opening Industrial Flow Control Valve


Flow Capacity Information





Ordering Information

Kingston Control Valves Part Number Codes



Product Notes

Storm Manufacturing reserves all rights. Product specifications and designs are subject to change without notice.

The information contained herein by Storm Manufacturing Group (SMG) is provided in good faith and as a product guide only. Further, SMG makes no representation as to the completeness or accuracy of the information contained herein. Any person or persons using the information contained herein must exercise their own judgement and consider all local, regional, national and global safety standards in evaluating valve selection options. Final application design and integration of Kingston Products are the sole responsibility of the end user.

